## NSN 5962-01-298-6406

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-298-6406

**Body Length:** 1.490 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** 0.217 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Console, plan position indicator display oj-194 (v)3/uya-4(v) **Features Provided:** Hermetically sealed and burn in and ultraviolet erasable and monolithic and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 17 input **Case Outline Source And Designator:** D-10 mil-m-38510 **Current Rating Per Characteristic:** 125.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 6.25 volts power source **Capitance Rating Per Characteristic:** 6.00 input picofarads and 12.00 output picofarads **Time Rating Per Chacteristic:** 250.00 nanoseconds access **Memory Device Type: Eprom Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

## NSN 5962-01-298-6406

Memory Microcircuit - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0