NSN 5962-01-298-7849

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-298-7849 **Overall Height:** Between 0.265 inches and 0.370 inches **Body Length:** Between 1.045 inches and 1.110 inches **Body Width:** Between 0.360 inches and 0.405 inches **Body Height:** Between 0.080 inches and 0.205 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Bipolar and edge triggered and asynchronous and synchronous and programmable and 3-state output and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 12 input **Current Rating Per Characteristic:** 185.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** Registered prom **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source **Capitance Rating Per Characteristic:** 5.00 input picofarads and 12.00 output picofarads **Memory Device Type:** Prom **Terminal Type And Quantity:** 22 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-298-7849

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0