

View Online at <https://aerobasegroup.com/nsn/5962-01-299-6398>

Body Length:

Between 0.540 inches and 0.560 inches

Body Width:

Between 0.442 inches and 0.458 inches

Body Height:

Between 0.054 inches and 0.088 inches

Maximum Power Dissipation Rating:

788.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Electrostatic sensitive and hermetically sealed and w/enable and burn in and programmable and erasable

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Metal oxide-semiconductor logic

Input Circuit Pattern:

22 input

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

6.0 volts power source

Time Rating Per Characteristic:

250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Rom

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

32 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0