

View Online at <https://aerobasegroup.com/nsn/5962-01-299-6401>

**Body Length:**

Between 0.540 inches and 0.560 inches

**Body Width:**

Between 0.442 inches and 0.458 inches

**Body Height:**

Between 0.060 inches and 0.120 inches

**Maximum Power Dissipation Rating:**

1.0 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and burn in and monolithic and programmable and ultraviolet erasable and w/enable and electrostatic sensitive

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

N-type metal oxide-semiconductor logic

**Input Circuit Pattern:**

16 input

**Case Outline Source And Designator:**

C-12 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.0 volts power source

**Time Rating Per Characteristic:**

250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Rom

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

32 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0