# NSN 5962-01-300-4983

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-300-4983

# Body Length: 0.785 inches Body Width: Between 0.220 inches and 0.310 inches Body Height: Between 0.140 inches and 0.185 inches Maximum Power Dissipation Rating: 125.0 milliwatts Operating Tempurature Range: -55.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius

\_\_\_\_\_

End Application:

5895-01-177-0790 master station

#### **Features Provided:**

Hermetically sealed and burn in and w/clock and electrostatic sensitive

#### Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

#### Output Logic Form:

Complementary-metal oxide-semiconductor logic

#### Input Circuit Pattern:

6 input

#### **Design Function And Quantity:**

1 generator

#### Case Outline Source And Designator:

D-1 mil-m-38510

#### **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

-0.3 volts power source and 15.0 volts power source

# Time Rating Per Chacteristic:

120.00 nanoseconds propagation delay time, low to high level output and 120.00 nanoseconds propagation delay time, high to low level output

# **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

# **Terminal Type And Quantity:**

14 printed circuit

Shelf Life:

N/a

# Unit Of Measure:

# NSN 5962-01-300-4983

Digital Microcircuit - Page 2 of 2

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0

