

View Online at <https://aerobasegroup.com/nsn/5962-01-300-5982>

**Body Length:**

1.490 inches

**Body Width:**

Between 0.500 inches and 0.610 inches

**Body Height:**

Between 0.172 inches and 0.217 inches

**Maximum Power Dissipation Rating:**

495.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and burn in and static operation and monolithic and bidirectional and w/enable and electrostatic sensitive

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

25 input

**Criticality Code Justification:**

Feat

**Case Outline Source And Designator:**

D-10 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

150.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Ram

**Memory Capacity:**

Unknown

**Special Features:**

Weapon system essential

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

28 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0