NSN 5962-01-300-7885

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-300-7885

	://aerobasegroup.com/nsn/5962-01-300-7885
Body Length:	
0.350 inches	
Body Width:	
0.350 inches	
Body Height:	
0.100 inches	
Maximum Power D	issipation Rating:
127.0 milliwatts	
Operating Tempur	ature Range:
-55.0/+125.0 degree	es celsius
Storage Tempurate	ure Range:
-65.0/+150.0 degree	elsius
Features Provided	:
Monolithic and bipol	ar and schottky
Inclosure Material:	
Ceramic	
Inclosure Configur	ation:
Leadless flat pack	
Output Logic Form	12
Transistor-transistor	logic
Input Circuit Patte	'n:
Quad 2 input	
Design Function A	nd Quantity:
4 selector, data, m	ultiplexer
Case Outline Sour	ce And Designator:
C-2 mil-m-38510	
Terminal Surface 1	reatment:
Solder	
Voltage Rating And	d Type Per Characteristic:
7.0 volts power sou	rce
Test Data Docume	nt:
81349-mil-m-38510	specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes co	mmercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and p	performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And	Quantity:
20 leadless	
Specification Data	
81349-mil-m-38510	/339 government specification
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
Yes - demil/mli	

NSN 5962-01-300-7885

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

