NSN 5962-01-300-9140

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-300-9140 **Body Length:** Between 0.442 inches and 0.460 inches **Body Width:** Between 0.442 inches and 0.460 inches **Body Height:** Between 0.060 inches and 0.100 inches **Maximum Power Dissipation Rating:** 2.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and hermetically sealed and burn in and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 4 input and 16 channel **Design Function And Quantity:** 1 multiplexer, analog **Case Outline Source And Designator:** C-4 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

44.0 volts power source

Time Rating Per Chacteristic:

1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A458a0