

View Online at <https://aerobasegroup.com/nsn/5962-01-300-9932>

Body Length:

Between 0.442 inches and 0.460 inches

Body Width:

Between 0.442 inches and 0.460 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

990.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and electrostatic sensitive and low power and schottky and 3-state output

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

13 input

Design Function And Quantity:

1 counter, up/down

Case Outline Source And Designator:

C-4 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

95.00 nanoseconds propagation delay time, low to high level output and 95.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A458a0