NSN 5962-01-301-4162

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-301-4162

Body Outside Diameter:
Between 0.595 inches and 0.605 inches
Body Height:
Between 0.150 inches and 0.180 inches
Maximum Power Dissipation Rating:
1500.0 milliwatts
Operating Tempurature Range:
55.0/+125.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
End Application:
Alq-135b
Features Provided:
Electrostatic sensitive and hermetically sealed and burn in and positive outputs
nclosure Material:
Metal
nclosure Configuration:
Can
nput Circuit Pattern:
2 input
Design Function And Quantity:
1 buffer
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
40.0 volts power source
Time Rating Per Chacteristic:
2.40 nanoseconds propagation delay time, low to high level output and 2.40 nanoseconds propagation delay time, high to low level output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
12 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
A458a0