## NSN 5962-01-301-4165

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-301-4165

view Online at https://aerobasegroup.com/hsh/5962-01-301-4165
Body Length:
Between 0.540 inches and 0.560 inches
Body Width:
Between 0.442 inches and 0.458 inches
Body Height:
Between 0.060 inches and 0.120 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Alq-135b
Features Provided:
Hermetically sealed and burn in and programmable and w/enable and bidirectional and erasable
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
N-type metal oxide-semiconductor logic
Input Circuit Pattern:
26 input
Case Outline Source And Designator:
C-12 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level
output
Memory Device Type:
Rom
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
32 leadless
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

## NSN 5962-01-301-4165

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0