NSN 5962-01-301-4862

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-301-4862

Body Length:
Between 0.342 inches and 0.358 inches
Body Width:
Between 0.342 inches and 0.358 inches
Body Height:
Between 0.060 inches and 0.100 inches
Maximum Power Dissipation Rating:
786.5 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Alq-135b
Features Provided:
Hermetically sealed and burn in and 3-state output and bipolar and schottky
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
18 input
Design Function And Quantity:
8 transceiver
Case Outline Source And Designator:
C-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
8.50 nanoseconds propagation delay time, low to high level output and 8.50 nanoseconds propagation delay time, high to low level output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 leadless
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-01-301-4862

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0