NSN 5962-01-301-5606

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-301-5606

Body Length:
Between 0.442 inches and 0.460 inches
Body Width:
Between 0.442 inches and 0.460 inches
Body Height:
Between 0.060 inches and 0.100 inches
Maximum Power Dissipation Rating:
55.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Alq-135b
Features Provided:
Hermetically sealed and burn in and w/clock and bipolar and w/enable and hybrid
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
12 input
Design Function And Quantity:
1 encoder and 1 decoder
Case Outline Source And Designator:
C-4 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
125.00 nanoseconds propagation delay time, low to high level output and 125.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
28 leadless

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5962-01-301-5606

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0