## NSN 5962-01-302-6189

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-302-6189
Body Length:
Between 0.442 inches and 0.460 inches
Body Width:
Between 0.442 inches and 0.460 inches
Body Height:
Between 0.060 inches and 0.100 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+155.0 degrees celsius
Features Provided:
Electrostatic sensitive and hermetically sealed and burn in and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
12 input
Design Function And Quantity:
1 buffer, noninverting
Case Outline Source And Designator:
C-4 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
8.50 nanoseconds propagation delay time, low to high level output and 8.50 nanoseconds propagation delay time, high to low level outp
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
28 leadless
Shelf Life:
N/a

Yes - demil/mli Fiig:

**Unit Of Measure:** 

Demilitarization:

A458a0