Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-302-9149

# **Body Length:**

1.060 inches

### **Body Width:**

0.310 inches

### **Body Height:**

0.185 inches

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **Features Provided:**

Burn in and hermetically sealed and monolithic and programmable

### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Dual-in-line

### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

16 input

# **Design Function And Quantity:**

1 gate, array

# **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

7.0 volts power source

### **Time Rating Per Chacteristic:**

30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

### Terminal Type And Quantity:

20 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

### Fiig:

A458a0