NSN 5962-01-303-3017

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-303-3017

Overall Length:

- 1.060 inches
- **Overall Height:**
- 0.400 inches

Overall Width:

- 0.320 inches
- **Body Length:**
- 1.060 inches

Body Width:

0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

2.0 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Bipolar and burn in and hermetically sealed and monolithic

Inclosure Material:

- Ceramic
- Inclosure Configuration:
- Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

- 16 input
- **Design Function And Quantity:**
- 1 gate, array
- Case Outline Source And Designator:
- D-8 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

12.0 volts power source

Time Rating Per Chacteristic:

30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

NSN 5962-01-303-3017

Digital Microcircuit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

