# NSN 5962-01-303-3541

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-303-3541

## **Overall Height:**

Between 0.325 inches and 0.400 inches

## **Body Length:**

0.405 inches

# Body Width:

Between 0.220 inches and 0.310 inches

#### **Body Height:**

Between 0.140 inches and 0.185 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-55.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and burn in and monolithic and positive outputs and electrostatic sensitive

#### Inclosure Material:

Ceramic

### Inclosure Configuration:

Dual-in-line

#### Input Circuit Pattern:

Dual 1 input

## **Design Function And Quantity:**

2 driver, power

#### Case Outline Source And Designator:

D-4 mil-m-38510

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

20.0 volts power source

#### Time Rating Per Chacteristic:

120.00 nanoseconds propagation delay time, low to high level output and 120.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

8 printed circuit

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0