NSN 5962-01-305-3042

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-305-3042

View Online at https://aerobasegroup.com/nsn/5962-01-305-3042
Body Length:
2.435 inches
Body Width:
Between 0.510 inches and 0.620 inches
Body Height:
Between 0.165 inches and 0.210 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and w/enable and w/clock
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
26 input
Design Function And Quantity:
1 sequencer
Case Outline Source And Designator:
D-14 mil-m-38510
Current Rating Per Characteristic:
30.00 milliamperes output
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
46.00 nanoseconds propagation delay time, low to high level output and 46.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
48 printed circuit
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-01-305-3042

Digital Microcircuit - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A458a0