## NSN 5962-01-305-3703

Memory Microcircuit - Page 1 of 2

24 printed circuit



View Online at https://aerobasegroup.com/nsn/5962-01-305-3703

| Overall Length:  |
|--|
| 1.290 inches   |
| Overall Height:  |
| 0.425 inches   |
| Overall Width:   |
| 0.620 inches   |
| Body Length:   |
| 1.290 inches   |
| Body Width:  |
| 0.610 inches   |
| Body Height:   |
| 0.210 inches   |
| Maximum Power Dissipation Rating:  |
| 1.0 watts  |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -55.0/+150.0 degrees celsius   |
| Features Provided:   |
| Burn in and monolithic and static operation  |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| Complementary-metal oxide-semiconductor logic  |
| Input Circuit Pattern:   |
| 15 input   |
| Case Outline Source And Designator:  |
| D-3 mil-m-38510  |
| Current Rating Per Characteristic:   |
| 70.00 milliamperes reverse current, dc absolute  |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 7.0 volts power source   |
| Memory Device Type:  |
| Ram  |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity:  |

## NSN 5962-01-305-3703

Memory Microcircuit - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A458a0