# NSN 5962-01-305-5361

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-305-5361

### **Body Length:** 1.490 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** Between 0.172 inches and 0.217 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and ultraviolet erasable and programmable and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 17 input **Case Outline Source And Designator:** D-10 mil-m-38510

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

6.5 volts power source

#### **Time Rating Per Chacteristic:**

250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

### Memory Device Type:

Rom

#### **Memory Capacity:**

Unknown

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### **Terminal Type And Quantity:**

28 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5962-01-305-5361

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

