## NSN 5962-01-306-5874

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/psp/5062-01-306-5874

| view Online at https://aerobasegroup.com/nsn/5962-01-306-5674  |
|--|
| Body Length:   |
| Between 1.380 inches and 1.420 inches  |
| Body Width:  |
| Between 0.560 inches and 0.600 inches  |
| Body Height:   |
| Between 0.040 inches and 0.180 inches  |
| Maximum Power Dissipation Rating:  |
| 800.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+125.0 degrees celsius   |
| Features Provided:   |
| Electrostatic sensitive and hermetically sealed and burn in and programmable and erasable and w/enable                               |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| N-type metal oxide-semiconductor logic   |
| Input Circuit Pattern:   |
| 24 input   |
| Time Rating Per Chacteristic:  |
| 350.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level |
| output   |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).                   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |