## NSN 5962-01-306-5876

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-306-5876

View Online at https://aerobasegroup.com/nsn/5962-01-306-5876
Body Length:
Between 0.875 inches and 0.905 inches
Body Width:
Between 0.245 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.175 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Asr-9, fa 10064
Features Provided:
Hermetically sealed and burn in and high performance and low power
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
16 input
Time Rating Per Chacteristic:
45.00 nanoseconds propagation delay time, low to high level output and 45.00 nanoseconds propagation delay time, high to low level
output
Special Features:
Reference data, 2a4a108u86, ti-6310.39, fa 10064, asr-9, vol 3, sec 8, pg 8-278
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A458a0