## NSN 5962-01-307-2587

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-307-2587

| view Offilite at https://aerobasegroup.com/nsn/0302-01-307-2307  |
|--|
| Overall Height:  |
| Between 0.325 inches and 0.400 inches  |
| Body Length:   |
| 1.280 inches   |
| Body Width:  |
| Between 0.220 inches and 0.310 inches  |
| Body Height:   |
| Between 0.140 inches and 0.185 inches  |
| Maximum Power Dissipation Rating:  |
| 650.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and burn in and programmable and w/clock   |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line Dual-in-line  |
| Output Logic Form:   |
| Complementary-metal oxide-semiconductor logic  |
| Input Circuit Pattern:   |
| 22 input   |
| Case Outline Source And Designator:  |
| D-9 mil-m-38510  |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 7.0 volts power source   |
| Time Rating Per Chacteristic:  |
| 55.00 nanoseconds propagation delay time, low to high level output and 55.00 nanoseconds propagation delay time, high to low level |
| output   |
| Memory Device Type:  |
| Pal  |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).                 |
| Terminal Type And Quantity:  |

N/a

**Unit Of Measure:** 

24 printed circuit

Shelf Life:

## NSN 5962-01-307-2587

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0