## NSN 5962-01-307-5953

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-307-5953

Body Length:
0.960 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Maximum Power Dissipation Rating:
250.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Weapon control system an/swg-3a
Features Provided:
Hermetically sealed and burn in and monolithic and w/clock and thermal overload protection
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
12 input
Design Function And Quantity:
1 modulator, regulator pulse width
Case Outline Source And Designator:
D-6 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
42.0 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
18 printed circuit
Specification Data:
81349-mil-m-38510/126 government specification
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

## NSN 5962-01-307-5953

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0