NSN 5962-01-308-3546

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-308-3546

20.0 watts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Radar set an/apn-59e Features Provided: Hermetically sealed and burn in and monolithic and adjustable and high voltage Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-sid-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Maximum Power Dissipation Rating:
-55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Radar set an/apn-59e Features Provided: Hermetically sealed and burn in and monolithic and adjustable and high voltage Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	20.0 watts
Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Radar set an/apn-59e Features Provided: Hermetically sealed and burn in and monolithic and adjustable and high voltage Inclosure Material: Metal Inclosure Configuration: Can Imput Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-sid-863 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Operating Tempurature Range:
-65.0/+150.0 degrees celsius End Application: Radar set an/apn-59e Features Provided: Hermetically sealed and burn in and monolithic and adjustable and high voltage Inclosure Material: Metal Inclosure Configuration: Can Imput Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-sid-863 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	-55.0/+125.0 degrees celsius
End Application: Radar set an/apn-59e Features Provided: Hermetically sealed and burn in and monolithic and adjustable and high voltage Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Storage Tempurature Range:
Radar set an/apn-59e Features Provided: Hermetically sealed and burn in and monolithic and adjustable and high voltage Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	-65.0/+150.0 degrees celsius
Features Provided: Hermetically sealed and burn in and monolithic and adjustable and high voltage Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	End Application:
Hermetically sealed and burn in and monolithic and adjustable and high voltage Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Radar set an/apn-59e
Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Features Provided:
Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Hermetically sealed and burn in and monolithic and adjustable and high voltage
Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Inclosure Material:
Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Metal
Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Inclosure Configuration:
1 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Can
Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Input Circuit Pattern:
1 regulator, voltage Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	1 input
Case Outline Source And Designator: To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Design Function And Quantity:
To-3 joint electron device engineering council Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	1 regulator, voltage
Current Rating Per Characteristic: 1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Case Outline Source And Designator:
1.50 amperes output Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	To-3 joint electron device engineering council
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Current Rating Per Characteristic:
Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	1.50 amperes output
Voltage Rating And Type Per Characteristic: 60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Terminal Surface Treatment:
60.0 volts input/output differential Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Solder
Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Voltage Rating And Type Per Characteristic:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	60.0 volts input/output differential
Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Test Data Document:
2 pin Shelf Life: N/a Unit Of Measure:	96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life: N/a Unit Of Measure:	Terminal Type And Quantity:
N/a Unit Of Measure:	2 pin
Unit Of Measure:	Shelf Life:
	N/a
Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
Yes - demil/mli	Yes - demil/mli
Fiig:	Fiig:
A458a0	A458a0