## NSN 5962-01-308-4176

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-308-4176

Body Outside Diameter:
0.370 inches
Body Height:
Between 0.240 inches and 0.260 inches
Maximum Power Dissipation Rating:
1.3 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and w/resistor and hybrid
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
1 input
Design Function And Quantity:
1 protector, overvoltage
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-50.0 volts power source
Time Rating Per Chacteristic:
10.00 nanoseconds propagation delay time, low to high level output and 10.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
Yes - demil/mli
Fiig:
A458a0