NSN 5962-01-308-8000

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-308-8000

Body Length:	
0.440 inches	
Body Width:	
Between 0.245	inches and 0.285 inches
Body Height:	
Between 0.045	inches and 0.085 inches
Maximum Pov	ver Dissipation Rating:
718.0 milliwatts	
Operating Ten	npurature Range:
-55.0/+125.0 de	egrees celsius
Storage Temp	urature Range:
-65.0/+165.0 de	egrees celsius
Features Prov	ided:
Hermetically se	aled and burn in and monolithic and negative outputs
Inclosure Mate	erial:
Ceramic	
Inclosure Con	figuration:
Flat pack	
Output Logic	Form:
Emitter-coupled	d logic
Input Circuit F	attern:
9 input	
Design Functi	on And Quantity:
1 counter, bina	ıry
Case Outline	Source And Designator:
F-5 mil-m-3851	0
Terminal Surfa	ace Treatment:
Solder	
Voltage Rating	And Type Per Characteristic:
-8.0 volts powe	er source
Time Rating P	er Chacteristic:
2.90 nanoseco	nds propagation delay time, low to high level output and 2.90 nanoseconds propagation delay time, high to low level output
Test Data Doc	ument:
96906-mil-std-8	883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type	And Quantity:
16 flat leads	
Shelf Life:	
N/a	
Unit Of Measu	re:
Demilitarizatio	n:
Yes - demil/mli	

NSN 5962-01-308-8000

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

