## NSN 5962-01-309-5043

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-309-5043

Body Length:
1.290 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
Between 0.150 inches and 0.210 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and programmable and w/enable and erasable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
N-type metal oxide-semiconductor logic
Input Circuit Pattern:
14 input
Case Outline Source And Designator:
D-3 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.3 volts power source and 6.0 volts power source
Time Rating Per Chacteristic:
250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level
output
Memory Device Type:
Rom
Memory Capacity:
Unknown
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5962-01-309-5043

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0