NSN 5962-01-309-8737

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-309-8737

| Overall Length: |
|--|
| Between 1.165 inches and 1.395 inches |
| Body Length: |
| Between 0.645 inches and 0.665 inches |
| Body Width: |
| Between 0.410 inches and 0.422 inches |
| Body Height: |
| Between 0.190 inches and 0.200 inches |
| Maximum Power Dissipation Rating: |
| 15.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and positive outputs |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Single-in-line |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 regulator |
| Case Outline Source And Designator: |
| To-257 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 35.0 volts power source |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 4 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

. ...9

A458a0