

View Online at <https://aerobasegroup.com/nsn/5962-01-309-8741>

Overall Height:

Between 0.325 inches and 0.400 inches

Body Length:

0.840 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.140 inches and 0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Bipolar and monolithic and burn in

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

6 input

Design Function And Quantity:

6 receiver

Case Outline Source And Designator:

D-2 mil-m-38510

Current Rating Per Characteristic:

5.00 milliamperes forward current, peak total value not applicable

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-16.0 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

500.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A458a0