# NSN 5962-01-310-4816

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-310-4816

## **Overall Length:**

- 1.060 inches
- **Overall Height:**
- 0.400 inches

# **Overall Width:**

- 0.320 inches
- **Body Length:**
- 1.060 inches

#### **Body Width:**

0.310 inches

#### **Body Height:**

- 0.185 inches
- **Maximum Power Dissipation Rating:**
- 2.0 watts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## End Application:

5895-01-206-2658 switch matrix

# Features Provided:

Bipolar and burn in and monolithic and programmed and w/register output

#### Inclosure Material:

Ceramic

## Inclosure Configuration:

Dual-in-line

## **Output Logic Form:**

Transistor-transistor logic

## Input Circuit Pattern:

16 input

## **Design Function And Quantity:**

1 gate, array

## Case Outline Source And Designator:

D-8 mil-m-38510

## **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 12.0 volts power source

# **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

# Terminal Type And Quantity:

20 printed circuit

# NSN 5962-01-310-4816

Digital Microcircuit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

