# NSN 5962-01-310-5452

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-310-5452

**Overall Length:** 

0.358 inches

**Overall Height:** 

0.100 inches

## **Overall Width:**

0.358 inches

**Body Length:** 

0.358 inches

#### **Body Width:**

0.358 inches

**Body Height:** 

0.088 inches

**Maximum Power Dissipation Rating:** 

60.5 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Bipolar and burn in and low power and monolithic and schottky

**Inclosure Material:** 

Ceramic

## Inclosure Configuration:

Leadless flat pack

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

7 input

#### **Design Function And Quantity:**

2 decoder, two to four line

#### **Case Outline Source And Designator:**

C-2 mil-m-38510

### **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

# Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

20 leadless

## Specification Data:

# NSN 5962-01-310-5452

Digital Microcircuit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

