## NSN 5962-01-310-7276

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-310-7276 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Operating Tempurature Range:** +0.0/+75.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and bipolar and w/enable and programmable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 70.00 nanoseconds propagation delay time, low to high level output and 70.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a

**Demilitarization:** 

Yes - demil/mli

**Unit Of Measure:** 

## NSN 5962-01-310-7276

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0