NSN 5962-01-310-8688

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-310-8688
Overall Height:
Between 0.275 inches and 0.350 inches
Body Length:
Between 1.010 inches and 1.050 inches
Body Width:
Between 0.250 inches and 0.290 inches
Body Height:
Between 0.090 inches and 0.185 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Support equipment, mx peacekeeper missile
Features Provided:
3-state output and monolithic and w/resistor
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Metal oxide-semiconductor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
8 driver, memory
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-310-8688

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0