NSN 5962-01-310-8691

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-310-8691

| Body Length: | |
|----------------------|--|
| 0.440 inches | |
| Body Width: | |
| 0.285 inches | |
| Body Height: | |
| 0.085 inches | |
| Maximum Power [| Dissipation Rating: |
| 332.8 milliwatts | |
| Operating Tempur | ature Range: |
| -55.0/+125.0 degre | es celsius |
| Storage Tempurat | ure Range: |
| -65.0/+150.0 degre | es celsius |
| Features Provided | : |
| Monolithic and w/or | pen collector and bipolar and programmable |
| Inclosure Material | : |
| Ceramic | |
| Inclosure Configu | ration: |
| Flat pack | |
| Output Logic Forn | n: |
| Transistor-transisto | r logic |
| Input Circuit Patte | rn: |
| 6 input | |
| Case Outline Sour | ce And Designator: |
| F-5 mil-m-38510 | |
| Terminal Surface | Treatment: |
| Solder | |
| Voltage Rating An | d Type Per Characteristic: |
| 7.0 volts power sou | urce |
| Time Rating Per C | hacteristic: |
| 50.00 nanoseconds | propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level |
| output | |
| Memory Device Ty | /pe: |
| Rom | |
| Test Data Docume | ent: |
| 96906-mil-std-883 : | standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And | d Quantity: |
| 16 flat leads | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |

NSN 5962-01-310-8691

Memory Microcircuit - Page 2 of 2

Fiig: A458a0

