

View Online at <https://aerobasegroup.com/nsn/5962-01-310-9841>

Body Length:

Between 0.745 inches and 0.780 inches

Body Width:

Between 0.240 inches and 0.280 inches

Body Height:

Between 0.115 inches and 0.195 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

1430-01-286-1314 guided missile

Features Provided:

Hermetically sealed and burn in and high speed and static operation and w/reset

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

2 input and 14 stage

Design Function And Quantity:

1 counter, binary

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0