NSN 5962-01-311-0646

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-311-0646

| Body Length: |
|---|
| Between 0.165 inches and 0.185 inches |
| Body Outside Diameter: |
| Between 0.300 inches and 0.370 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Low noise and w/resistor and monolithic |
| Inclosure Material: |
| Metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 amplifier, chopper |
| Current Rating Per Characteristic: |
| 3.00 milliamperes reverse current, dc absolute |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Chopper stabilized operational amplifier |
| Voltage Rating And Type Per Characteristic: |
| 18.0 volts power source and 18.0 volts power source |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) |
| Terminal Type And Quantity: |
| 8 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |