NSN 5962-01-312-2590

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-312-2590

Body Length:	
Between 0.640 inches and	0.662 inches
Body Width:	

Between 0.640 inches and 0.662 inches

Body Height:

Between 0.064 inches and 0.120 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Weapon control system an/swg-3a

Features Provided:

Hermetically sealed and burn in and asynchronous and w/clock

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Metal oxide-semiconductor logic

Input Circuit Pattern:

26 input

Design Function And Quantity:

1 receiver, asynchronous and 1 transmitter

Case Outline Source And Designator:

C-5 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

6.0 volts power source

Time Rating Per Chacteristic:

350.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

44 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

NSN 5962-01-312-2590

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0