NSN 5962-01-313-7194

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-313-7194

| Overall Length: |
|--|
| 0.358 inches |
| Overall Height: |
| 0.100 inches |
| Overall Width: |
| 0.358 inches |
| Body Length: |
| 0.358 inches |
| Body Width: |
| 0.358 inches |
| Body Height: |
| 0.088 inches |
| Maximum Power Dissipation Rating: |
| 55.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Bipolar and burn in and low power and schottky |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Leadless flat pack |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 5 input |
| Design Function And Quantity: |
| 1 decoder |
| Case Outline Source And Designator: |
| C-2 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Test Data Document: |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 20 leadless |

Specification Data:

81349-mil-m-38510/307 government specification

NSN 5962-01-313-7194

Digital Microcircuit - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0