# NSN 5962-01-314-3870

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-314-3870

## **Overall Height:**

Between 0.060 inches and 0.100 inches

## **Body Length:**

Between 0.342 inches and 0.358 inches

# Body Width:

Between 0.342 inches and 0.358 inches

### **Body Height:**

Between 0.050 inches and 0.088 inches

## **Maximum Power Dissipation Rating:**

137.5 milliwatts

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Bipolar and low power and schottky and monolithic and 3-state output and electrostatic sensitive

#### Inclosure Material:

Ceramic

## Inclosure Configuration:

Leadless flat pack

# **Output Logic Form:**

Transistor-transistor logic

# **Design Function And Quantity:**

8 buffer and 8 driver

## **Case Outline Source And Designator:**

C-2 mil-m-38510

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

## Test Data Document:

96909-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### **Terminal Type And Quantity:**

20 leadless

#### Shelf Life:

N/a

## Unit Of Measure:

--

### Demilitarization:

Yes - demil/mli

# Fiig:

A458a0