## NSN 5962-01-314-7454

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-314-7454

| Maximum Power Dissipation Rating:  |
|--|
| 500.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+125.0 degrees celsius   |
| Features Provided:   |
| Internally trimmed and monolithic and electrostatic sensitive  |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Leadless flat pack   |
| Input Circuit Pattern:   |
| 7 input  |
| Design Function And Quantity:  |
| 1 multiplier, four quadrant  |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 22.0 volts power source  |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity:  |
| 20 leadless  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |
|  |