## NSN 5962-01-314-9179

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-314-9179

Body Length:
Between 0.342 inches and 0.358 inches
Body Width:
Between 0.342 inches and 0.358 inches
Body Height:
Between 0.060 inches and 0.100 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Electrostatic sensitive and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 amplifier, operational, linear
Case Outline Source And Designator:
C-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
20.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 leadless
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:

A458a0