## NSN 5962-01-314-9699

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-314-9699

Overall Height: 0.100 inches Overall Width: 0.410 inches Body Length: 0.410 inches Body Width: 0.410 inches Body Width: 0.410 inches Body Height: 0.088 inches Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510 Terminal Surface Treatment:
Overall Width:  0.410 inches  Body Length: 0.410 inches  Body Width: 0.410 inches  Body Height: 0.088 inches  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input  Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Overall Width:  0.410 inches  Body Length:  0.410 inches  Body Width:  0.410 inches  Body Height:  0.088 inches  Operating Tempurature Range:  -55.0/+125.0 degrees celsius  Storage Tempurature Range:  -65.0/+150.0 degrees celsius  Features Provided:  Burn in and electrostatic sensitive and monolithic Inclosure Material:  Ceramic  Inclosure Configuration:  Leadless flat pack  Input Circuit Pattern:  Quad 2 input  Design Function And Quantity:  4 amplifier, operational, general purpose  Case Outline Source And Designator:  C-3 mil-m-38510
0.410 inches  Body Length: 0.410 inches  Body Width: 0.410 inches  Body Height: 0.088 inches  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input  Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Body Length: 0.410 inches Body Width: 0.410 inches Body Height: 0.088 inches Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
0.410 inches  Body Width: 0.410 inches  Body Height: 0.088 inches  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Body Width: 0.410 inches Body Height: 0.088 inches Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
0.410 inches  Body Height: 0.088 inches  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input  Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Body Height:  0.088 inches  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input  Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
-55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
-65.0/+150.0 degrees celsius  Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Features Provided: Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Burn in and electrostatic sensitive and monolithic Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Leadless flat pack Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Input Circuit Pattern: Quad 2 input  Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
Quad 2 input  Design Function And Quantity:  4 amplifier, operational, general purpose  Case Outline Source And Designator:  C-3 mil-m-38510
Design Function And Quantity: 4 amplifier, operational, general purpose Case Outline Source And Designator: C-3 mil-m-38510
4 amplifier, operational, general purpose  Case Outline Source And Designator:  C-3 mil-m-38510
Case Outline Source And Designator: C-3 mil-m-38510
C-3 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
22.0 volts power source
Terminal Type And Quantity:
20 leadless
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A458a0