NSN 5962-01-315-3322

Linear Microcircuit - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5962-01-315-3322

| Overall Height: |
|---|
| Between 0.665 inches and 0.935 inches |
| Body Length: |
| Between 0.016 inches and 0.024 inches |
| Body Outside Diameter: |
| Between 0.165 inches and 0.185 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic |
| Inclosure Material: |
| Metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| Dual 2 input |
| Design Function And Quantity: |
| 2 amplifier, operational, general purpose |
| Case Outline Source And Designator: |
| A-1 mil-m-38510 |
| Current Rating Per Characteristic: |
| 3.00 milliamperes reverse current, dc absolute |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 22.0 volts power source |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) |
| Terminal Type And Quantity: |
| 8 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5962-01-315-3322

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0