NSN 5962-01-315-3328

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-315-3328

| Overall Height: |
|---|
| Between 0.357 inches and 0.432 inches |
| Body Length: |
| 1.490 inches |
| Body Width: |
| Between 0.500 inches and 0.610 inches |
| Body Height: |
| Between 0.172 inches and 0.217 inches |
| Maximum Power Dissipation Rating: |
| 1.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 5998-01-284-8573 electronic components assembly |
| Features Provided: |
| Monolithic and parallel operation and w/reset |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 13 input |
| Case Outline Source And Designator: |
| D-10 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Memory Device Type: |
| First-in first-out |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) |
| Terminal Type And Quantity: |
| 28 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5962-01-315-3328

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0