NSN 5962-01-316-3523

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-316-3523

Body Length:
Between 0.442 inches and 0.460 inches
Body Width:
Between 0.442 inches and 0.460 inches
Body Height:
Between 0.060 inches and 0.100 inches
Maximum Power Dissipation Rating:
170.5 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and 3-state output and low power and schottky and w/clear and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 7 input
Design Function And Quantity:
2 latch, d
Case Outline Source And Designator:
C-4 mil-m-38510
Current Rating Per Characteristic:
21.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
28 leadless
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-01-316-3523

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0