## NSN 5962-01-316-5459

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-316-5459

Overall Length:
0.358 inches
Overall Height:
0.100 inches
Overall Width:
0.358 inches
Body Length:
0.358 inches
Body Width:
0.358 inches
Body Height:
0.088 inches
Maximum Power Dissipation Rating:
25.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Bipolar and burn in and cascadable and low power and monolithic and schottky and w/clear and w/clock
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
9 input
Design Function And Quantity:
6 flip-flop, d-type
Case Outline Source And Designator:
C-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

20 leadless

**Specification Data:** 

81349-mil-m-38510/301 government specification

## NSN 5962-01-316-5459

Digital Microcircuit - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0