NSN 5962-01-316-5950

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-316-5950

Overall Length:

0.358 inches

Overall Height:

0.100 inches

Overall Width:

0.358 inches

Body Length:

0.358 inches

Body Width:

0.358 inches

Body Height:

0.088 inches

Maximum Power Dissipation Rating:

6.1 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Aircraft, hawkeye e-2c; aircraft, harrier av-8b; missile, advanced medium range air-to-air (amraam)/aim120a

Features Provided:

Burn in and bipolar and low power and monolithic and schottky

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Triple 3 input

Criticality Code Justification:

Feat

Design Function And Quantity:

3 gate, nand

Case Outline Source And Designator:

C-2 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Special Features:

Weapon system essential

NSN 5962-01-316-5950

Digital Microcircuit - Page 2 of 2



Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:**

20 leadless

Specification Data:

81349-mil-m-38510/300 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0