NSN 5962-01-316-5952

Digital Microcircuit - Page 1 of 2

20 leadless



View Online at https://aerobasegroup.com/nsn/5962-01-316-5952

Overall Length:
0.358 inches
Overall Height:
0.100 inches
Overall Width:
0.358 inches
Body Length:
0.350 inches
Body Width:
0.350 inches
Body Height:
0.100 inches
Maximum Power Dissipation Rating:
700.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and low power and schottky and 3-state output
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 register, d-type
Case Outline Source And Designator:
C-2 mil-m-38510
Current Rating Per Characteristic:
30.00 milliamperes forward current, nonrepetitive, peak total value absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts input
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

NSN 5962-01-316-5952

Digital Microcircuit - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0