NSN 5962-01-316-6886

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-316-6886

Overall Height:
Between 0.325 inches and 0.400 inches
Body Length:
0.785 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and low noise
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
8 input
Design Function And Quantity:
4 amplifier, operational, general purpose
Case Outline Source And Designator:
D-1 mil-m-38510
Current Rating Per Characteristic:
11.00 milliamperes input
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, linear, radiation hardened, low noise, quad operational amplifiers, monolithic silicon
Voltage Rating And Type Per Characteristic:
18.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5962-01-316-6886

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0